Consult Heyco for Colors Other Than Black

HEYCo-molded™ Liquid Tight Break-Thru Plugs

Mounting Hole Diameter Range: .500″ (12,7 mm) to 1.500″ (38,1 mm)

Small Packs Available

PANEL DIMENSIONS Thickness at Locking Finger Steps		Mounting Hole Diameter*		CABLE DIAMETER RANGE		PART NO. Black	PACKAGING BULK (Std)	SMALL PACK**	DESCRIPTION	PART DIMENSIONS A Head Diameter		B Overall Height	
in.	mm.	in.	mm.	in.	mm.					in.	mm.	in.	mm.
With Five Locking Finger Steps for Panels up to .063″ (1,6 mm) Thick													
.020	0,5	.500	12,7	.080 - .200	2,0 - 5,1	**C2008**	1000	10	LTBP 500-063	.92	23,4	.32	8,1
.032	0,8	.625	15,9	.130 - .375	3,3 - 9,5	**C2012**	1000	10	LTBP 625-063	1.03	26,2		
.040	1,0	.750	19,1	.175 - .400	4,4 - 10,2	**C2016**	1000	10	LTBP 750-063	1.15	29,2		
.048	1,2	.875	22,2	.130 - .450	3,3 - 11,4	**C2020**	1000	10	LTBP 875-063	1.28	32,5		
.063	1,6	1.000	25,4	.200 - .715	5,1 - 18,2	**C2022**	1000	10	LTBP 1000-063	1.43	36,3		
		1.093	27,8	.250 - .765	6,4 - 19,4	**C2024**	1000	10	LTBP 1093-063	1.53	38,9		
With Seven Locking Finger Steps for Panels from .063″ (1,6 mm) to .250″ (6,4 mm) Thick													
.063	1,6	.500	12,7	.080 - .200	2,0 - 5,1	**C2058**	1000	10	LTBP 500-250	.92	23,4	.63	15,9
.080	2,0	.625	15,9	.130 - .375	3,3 - 9,5	**C2062**	1000	10	LTBP 625-250	1.03	26,2		
.094	2,4	.750	19,1	.175 - .400	4,4 - 10,2	**C2066**	1000	10	LTBP 750-250	1.15	29,2		
.125	3,2	.875	22,2	.130 - .450	3,3 - 11,4	**C2070**	1000	10	LTBP 875-250	1.28	32,5		
.157	4,0	1.000	25,4	.200 - .715	5,1 - 18,2	**C2072**	1000	10	LTBP 1000-250	1.43	36,3		
.200	5,1	1.093	27,8	.250 - .765	6,4 - 19,4	**C2074**	1000	10	LTBP 1093-250	1.53	38,9		
.250	6,4	1.375	34,9	.300 - .950	7,6 - 24,1	**C2080**	1000	10	LTBP 1375-250	1.80	45,7	.67	17,0
		1.500	38,1	.375 - 1.060	9,5 - 26,9	**C2082**	1000	10	LTBP 1500-250	1.93	49,0		

Standard color black. Consult Heyco for other colors.
*Consult Heyco for other Mounting Hole Diameters. Our Axcell Rapid Response Team is ready to meet your requirements.
*To order Small Packs, please add the suffix -P to Part No., e.g., C2008-P

- These **co-molded** nylon and elastomer parts function as **Liquid Tight Plugs** with an IP 67/68 rating, yet can be pierced by **round wire, cable or tubing** to function as **Liquid Tight Bushings** with the same resulting IP 67/68 rating.
- **Certified by UL under UL 635**
- For use in panels as thin as .020″ (0,5 mm) and as thick as .250″ (6,4 mm).
- Provide liquid tight closure when used as a plug. When pierced, function as a liquid tight bushing that convert raw edged holes to smooth, neat, insulated holes.
- Used as a liquid tight bushing, HEYCo-molded Liquid Tight Break-Thru Plugs insulate and mechanically protect electrical and telecommunications cable, tubing, hose, rope, and utility lines.
- Locking fingers snap into holes with fingertip pressure.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Available in multiple sizes for use in .500″ (12,7 mm) to 1.500″ (38,1 mm) diameter holes.





Materials	Nylon 6/6 and TPE
Certifications	Recognized under the Component Program of Underwriters' Laboratories File E15331
Flammability Rating	HB
Temperature Range	-40°F (-40°C) to 212°F (100°C)
IP Rating	IP 67/68

1-800-526-4182 • 732-286-1800 (NJ) • FAX: 732-244-8843 • www.heyco.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Heyco:

C2008 C2012 C2016 C2020 C2022 C2024 C2074 C2066 C2062 C2082 C2072 C2070 C2080 C2058 C2072-P C2080-P C2022-P C2082-P C2070-P C2082JJ C2058-P C2024-P C2008-P C2020-P C2016-P C2012-P C2062-P C2066-P C2074-P