

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION



© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC
ES



DIST
00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
E14		REVISED PER ECR-19-012828	29JAN19	T.Z	S.L



PC BOARD MOUNTING DIMENSIONS





- ① MATERIAL:
SHELL- STAINLESS STEEL.
CONTACTS- COPPER ALLOY.
HOUSING: UL 94V-0 RATED, THERMOPLASTIC, COLOR SEE TABLE.
- ② PLATING:
CONTACTS: 0.076μm MINIMUM GOLD OVER 0.76μm MINIMUM PALLADIUM-NICKEL ON MATING AREA.
3.8μm MINIMUM MATTE TIN ON SOLDER TAILS.
BOTH OVER 1.27μm MINIMUM NICKEL.
CONTACT ALTERNATE PLATING: 0.76μm MIN GOLD ON MATING AREA, 3.80μm MIN MATTE TIN ON SOLDER TAILS, BOTH OVER 1.27μm MIN NICKEL.
SHELL: 2~5μm MINIMUM BRIGHT TIN
- ③ DATUM AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- ④ RECOMMENDED PC BOARD THICKNESS OF 1.57.
- ⑤ PLATING:
CONTACTS:0.76μm MINIMUM PALLADIUM-NICKEL ON MATING AREA.
3.8μm MINIMUM MATTE TIN ON SOLDER TAILS.
BOTH OVER 1.27μm MINIMUM NICKEL.
SHELL: 2~5μm MINIMUM BRIGHT TIN

⑤	YES	2.84	BLACK	2-292303-0
②	YES	2.29	BLACK	1-292303-9
②	NO	3.81	BLACK	1-292303-5
②	NO	3.56	BLACK	1-292303-4
②	NO	3.20	BLACK	1-292303-3
②	YES	3.30	BLACK	1-292303-2
②	YES	2.29	BLACK	292303-6
②	YES	2.84	NATURAL	292303-5
②	YES	2.84	BLACK	292303-4
②	NO	2.84	NATURAL	292303-3
②	NO	2.29	BLACK	292303-2
②	NO	2.84	BLACK	292303-1
CONTACT PLATING		HIGH TEMPERATURE COMPATIBLE	D	HOUSING COLOR
				PART NUMBER



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J.JIANG 19FEB04	TE Connectivity		
		CHK S.YAO 19FEB04			
DIMENSIONS: mm		APVD T.SASAKI 19FEB04	NAME		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC 108-60034	RECEPTACLE ASSEMBLY RIGHT ANGLE, 4 POSITION, T/H & SMT USB, LEAD FREE VERSION		
0 PLC ± - 1 PLC ± - 2 PLC ± 0.25 3 PLC ± - 4 PLC ± - ANGLES ± - FINISH		APPLICATION SPEC			
MATERIAL 1		WEIGHT -	SIZE A2	CAGE CODE 00779	DRAWING NO C=292303
SEE TABLE		CUSTOMER DRAWING	SCALE 5:1	SHEET 1 OF 4	REV E14

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	OWN	APVD
ES	00		—	SEE SHEET 1	—	—	—




- ⚠ MATERIAL:
- ⑪ SHELL- STAINLESS STEEL
CONTACTS- COPPER ALLOY.
HOUSING: UL 94V-0 RATED, THERMOPLASTIC, COLOR SEE TABLE.
- ⚠ PLATING:
- CONTACTS: 0.076 μm MINIMUM GOLD OVER 0.76 μm MINIMUM PALLADIUM-NICKEL ON MATING AREA.
3.8 μm MINIMUM MATTE TIN ON SOLDER TAILS.
BOTH OVER 1.27 μm MINIMUM NICKEL.
CONTACT ALTERNATE PLATING: 0.76 μm MIN GOLD ON MATING AREA, 3.80 μm MIN MATTE TIN ON SOLDER TAILS, BOTH OVER 1.27 μm MIN NICKEL.
SHELL: 2~5 μm MINIMUM BRIGHT TIN
- ⚠ RECOMMENDED PC BOARD THICKNESS OF 1.42.

RECOMMENDED PC BOARD MOUNTING LAYOUT ⚠
(TOLERANCE=±0.05)



YES	OBSELETE	BLACK	3-292303-1	⑪
YES		BLACK	1-292303-1	
YES		NATURAL	292303-7	
HIGH TEMPERATURE COMPATIBLE		HOUSING COLOR	PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DMN J.JIANG 19FEB04	TE Connectivity		
		CHK S.YAO 19FEB04			
		APVD T.SASAKI 19FEB04	NAME RECEPTACLE ASSEMBLY RIGHT ANGLE, 4 POSITION, T/H & SMT USB, LEAD FREE VERSION		
		PRODUCT SPEC 108-60034			
		APPLICATION SPEC			
		WEIGHT -	SIZE A2	CAGE CODE 00779	DRAWING NO C=292303
		CUSTOMER DRAWING	SCALE 5:1	SHEET 2 OF 4	REV E14





- RECOMMENDED PC BOARD THICKNESS OF 1.2.

NATURAL	292303-8
HOUSING COLOR	PART NUMBER

		TE Connectivity	
NAME			
RECEPTACLE ASSEMBLY RIGHT ANGLE, 4 POSITION, T/H & SMT USB, LEAD FREE VERSION			
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-292303	—
		SCALE 5:1	SHEET 3 OF 4 REV F14

P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	SEE SHEET 1	-	-	-




D



RECOMMENDED MOUNTING PANEL CUTOUT

C


B



RECOMMENDED PC BOARD MOUNTING LAYOUT (TOLERANCE=±0.05)

A

YES	BLACK	1-292303-6
YES	NATURAL	292303-9
HIGH TEMPERATURE COMPATIBLE	HOUSING COLOR	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J.JIANG 19FEB04	 TE Connectivity			
DIMENSIONS: mm		CHK S.YAO 19FEB04	NAME RECEPTACLE ASSEMBLY RIGHT ANGLE, 4 POSITION, T/H & SMT USB, LEAD FREE VERSION			
	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± 0.25 3 PLC ± - 4 PLC ± - ANGLES ± -	APVD T.SASAKI 19FEB04				
		PRODUCT SPEC 108-60034 APPLICATION SPEC -				
MATERIAL 	FINISH 	WEIGHT -	SIZE A2	CAGE CODE 00779	DRAWING NO C-292303	RESTRICTED TO -
CUSTOMER DRAWING			SCALE 5:1	SHEET 4 OF 4	REV E14	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-292303-1](#)