

4		3		2		1													
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		LOC		DIST		REVISIONS											
© COPYRIGHT - By -		ALL RIGHTS RESERVED.		G		14		P		LTR		DESCRIPTION		DATE		DWN		APVD	
										G1		REVISED PER ECO-11-004917		11MAR11		RK		HMR	

1. INSULATION DIA
.170 MAX

2. FITS TAB .020 THK

100		LOOSE PC,BOX		8-640929-1	
-		TAPE MOUNTED		640929-2	
-		LOOSE PIECE		640929-1	
QTY		PACKAGE TYPE		PART NO	

AMP INCORPORATED CUSTOMER SERVICE SYSTEM		MAX RECOMMENDED OPERATING TEMPERATURE:		THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L OLMEDA 13NOV95		TE Connectivity									
FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS		PRODUCT INFORMATION CENTER 1-800-522-6752		DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:						CHK M ELLIS 15NOV95					
FOR APPLICATION TOOLING INFORMATION		TOOLING ASSISTANCE CENTER 1-800-722-1111		VOLTAGE RATING:		0 PLC ± - 1 PLC ± - 2 PLC ± .015 3 PLC ± - 4 PLC ± - ANGLES ± -		APVD B BARE 15NOV95		NAME RECEPTACLE, 110 SERIES, FASTON™, PIDG™, WIRE SIZE, 16-14 AWG							
FOR ORDER ENTRY		1-800-526-5142		CIRCULAR MIL AREA:		FINISH BODY,PRE-TIN		PRODUCT SPEC - APPLICATION SPEC - WEIGHT -				SIZE A3		CAGE CODE 00779		DRAWING NO C-640929	
						MATERIAL BODY,BRASS .016 SLV,NYLON,COLOR, BLUE		CUSTOMER DRAWING		SCALE NTS		SHEET 1 OF 1		REV G1			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[640929-1](#)