

	Doc. No.	DC Socket-106	Page No.	1/8
	Date Issued	2020-04-06	Prepared by	Shanzha
	Date revised	2024-09-24	checked by	Sangshen
Product Specification	Rev. No.	A1	Approved by	Willy
Title: DC Socket				

1. SCOPE（适用范围）

This specification covers the performance, tests and quality requirements for the DC Socket .
(本规范涵盖了 DC Socket 的性能、测试和质量要求。)

2. PRODUCT DESCRIPTION（产品描述）

DESCRIPTION（描述）	Part Number（料号）
DC 连接器 W12.3xD10xH11,内芯 2.5,8A 24V 直脚	DC-042C-Z-2.5

3. APPLICABLE DOCUMENT（适用文件）

The following documents form a part of this specification to the extent specified herein. In the event of conflict between the requirements of this specification and the product drawing, the product drawing shall take precedence. In the event of conflict between the requirements of this specification and the referenced documents, this specification shall take precedence.（下列文件构成本规范的一部分，在此规定的范围内。本规范要求与产品图纸有冲突时，以产品图纸为准。如果本规范的要求与参考文件发生冲突，应以本规范为准。）

4. REQUIREMENTS（要求）

4.1. Design and Structure（设计和结构）

Product shall be of the design, structure and physical dimensions specified on the applicable product drawing.（产品的设计、结构和物理尺寸参考所适用的产品图纸）

4.2. Materials/ Finish (材料/表面处理)

Materials used in the structure of product shall be as specified on the applicable product drawing. (产品结构中使用的材料参考所适用的产品图纸)

4.3. Ratings（额定功率）

Item（项目）	Standard（标准）
Rated Voltage (Maximum)额定电压	24V DC
Rated Current (Maximum)额定电流	8A
Operating temperature range工作温度范围	-25℃～+70℃ From -25 to +70 egree centigrade

	Doc. No.	DC Socket-106	Page No.	2/8
	Date Issued	2020-04-06	Prepared by	Shanzha
	Date revised	2024-09-24	checked by	Sangshen
Product Specification	Rev. No.	A1	Approved by	Willy
Title: DC Socket				

5.0 TEST STANDARD （测试条件）

5.1 Unless otherwise specified, the standard range of atmospheric conditions for making measurements and tests are as follows （除另有说明外，用以进行测量和测试的标准环境条件范围如下）

Ambient temperature （环境温度）: 5℃ to 35℃

Normal humidity （正常湿度）: 45% to 85%

Air pressure （气压）: 86Kpa to 106Kpa

5.2 However if doubt arises on the decision based on the measured Values under the above-mentioned Conditions.The following conditions shall be employed: （但是在对判定产生疑问时,按下述状态实施）

Temperature （温度）: 20±2℃

Relative humidity （相对湿度）: 65±5%

Air pressure （气压）: 86Kpa to 106Kpa

6. PERFORMANCE AND TEST DESCRIPTION （性能和测试类型）

6.1 APPEARANCE （外观）

ITEM	DESCRIPTION （类型）	TEST CONDITION （测试条件）	REQUIREMENT （要求）
1	Appearance 外观	Visual. 目视	Should not have any flaw Scratch discoloration and crushed.无任何裂痕、刮伤、 污染和变形

6.2 ELECTRICAL （电气）

ITEM	DESCRIPTION （类型）	TEST CONDITION （测试条件）	REQUIREMENT （要求）
1	Contact resistance. 接触电阻	Measured at low current (100mA or less). （在低电流（≤100mA）条件下测试。）	30 mΩ Max.

	Doc. No.	DC Socket-106	Page No.	3/8
	Date Issued	2020-04-06	Prepared by	Shanzha
	Date revised	2024-09-24	checked by	Sangshen
Product Specification	Rev. No.	A1	Approved by	Willy
Title: DC Socket				

2	Insulation Resistance. 绝缘电阻	Apply a voltage of 100V DC for 1 MIN to following portions after which measurement shall be made 输入 DC 100V,一分钟, 按以下接触方法测试: (1). Between body and conductor. 插座体与排脚之间 (2). Between conductors not to be contact. 不接触的排脚之间 (3). Between conductors not to be when plug is inserted DC 100V 1 MIN. 插头插入时不接触的排脚之间	100 M min.
3	Dielectric strength. (耐电压)	AC 500V ims(50~60Hz)for 1 MIN trip current: 0.5mA 输入 AC 5000V(50~60Hz)/min 电压一分钟, 漏电电流为: 0.5mA (1). Between body and conductor. 插座体与排脚之间 (2). Between conductors not to be contact. 不接触的排脚之间 (3). Between conductors not to be when plug is inserted DC 500V 1 MIN. 插头插入时不接触的排脚之间	There shall be no breakdown. 无击穿、闪烁现象

6.3 MECHANICAL (机械)

ITEM	DESCRIPTION (类型)	TEST CONDITION (测试条件)	REQUIREMENT (要求)
1	Insertion Force (插入力)	Measurement shall be made after connecting and disconnecting using stand plug gauge 3 times . 依据标准的 PLUG GAUGE 做第 3 次插拔后测试	3~25N
2	Extraction Force (拔出力)	Measurement shall be made after connecting and disconnecting using stand plug gauge 3 times . 依据标准的 PLUG GAUGE 做第 3 次插拔后测试	3~25N

	Doc. No.	DC Socket-106	Page No.	4/8
	Date Issued	2020-04-06	Prepared by	Shanzha
	Date revised	2024-09-24	checked by	Sangshen
Product Specification	Rev. No.	A1	Approved by	Willy
Title: DC Socket				

3	Terminal Strength (端子强度)	A static load of 5N(0.5kgf)/m shall be applied to the tip of the terminal for 1 MIN in any direction. 向排脚先端的任意一个方向施加 1 分钟 5N(0.5kgf)的力度	There shall be no damage to the terminal such as cracks,Looseness or play electrical ,And mechanical characteristics shall be satisfied.在排脚中没有裂开,松动等异常,满足于机械,电气性能
4	Life Test (寿命测试)	Connection and disconnection shall be made with the mating plug and jack for 5'000 cycles at a speed of 10 to 25 cycles/MIN. 将结合了的标准 Plug (尽量要近于中心的) 在 1 分钟以 10~25 的速度,进行 5'000 次的插入,拔出	Contact resistance 接触电阻: 30 mΩ Max. Extraction Force 拔出力: 3~25N Mechanical and electrical characteristics shall be satisfied. 满足于机械和电气性能

6.4 ENVIRONMENTAL (环境)

ITEM	DESCRIPTION (类型)	TEST CONDITION (测试条件)	REQUIREMENT (要求)
1	Solder ability (可焊性)	Immerse the solder pin of the connector in solder bath at 245±5℃ for 3±0.5sec. After dipped the pin in the flux 5sec. 将端子脚浸入助焊剂中5秒,然后将端子脚浸入245±5℃的锡炉中3±0.5秒	Solder wetting: 95% of immersed area must show voids, Pin holes. 锡附着面积应超过浸入表面积95%以上
2	Resistance to Soldering Heat (焊锡耐热性)	The contact of terminal shall be tested resistance to soldering heat in the following conditions. After Resistance to soldering heat test Contact Resistance. 端子应在下列条件下做耐吃锡性试验,焊锡耐热性后试接触阻抗 In case of solder iron (2 time) 电烙铁(两次) Temperature 温度:350℃+/-5℃ Time 时间: 5s+/-1s	Should not have any flaw scratch and crack. 无任何裂痕、刮伤和破裂

	Doc. No.	DC Socket-106	Page No.	5/8
	Date Issued	2020-04-06	Prepared by	Shanzha
	Date revised	2024-09-24	checked by	Sangshen
Product Specification	Rev. No.	A1	Approved by	Willy
Title: DC Socket				

3	Humidity Test (耐湿测试)	The jack shall be stored at a temperature of 40±2℃ and a humidity of 90% to 96% for 96 Hr,Then the jack shall be maintained at stand atmospheric condition for 1 Hr for other procedures. 放置于 40±2℃的相应湿度为 90~96% Hr 环境中 96 小时后, 再将样品放在正常环境中 1 小时后进行测试	There shall be no damage on appearance. Mechanical and electrical characteristics shall be satisfied. 外观无异常, 满足于机械和电气性能
4	Heat Resistance Test (耐热测试)	The jack shall be stored at a temperature of 70±2℃ for 96 Hours,And then the jack shall be maintained at stand atmospheric condition for 1 Hr for other procedures. 放置于70±2℃ 中96 小时后, 再将样品放在正常环境中1小时后进行测试	
5	Cold Resistance Test (耐寒测试)	The jack shall be stored at a temperature of -25±3℃ for 96 hours and then it shall be subjected to the controlled recovery conditions for 1 hour after which. 放置于-25±3℃ 中 96 小时后, 再将样品放在正常环境中 1 小时后进行测试	There shall be no damage on appearance. Mechanical and electrical characteristics shall be satisfied. 外观无异常, 满足于机械和电气性能
6	Salt Spray Test (盐雾试验)	1. Testing bath 测试容器 : The temperature shall 35±2℃ in the ambient of the specimen during the test. 在测试过程中, 产品周围环境温度 35±2℃ 2. Spray apparatus 喷雾设备 : The apparatus shall capable of producing fine dense mist uniformly.盐雾均匀喷出 3. Salt water 盐水 :The concentration of the salt water shall adjusted at 5±1% weight ratio at 35±2℃ . 盐水要在 35±2℃ 温度条件下, 调整在 5±1%比例范围内 4. Testing time 测试时间 : 24±0.5 hours. After washed in water . The sample shall left alone for 1 or 2 hours in a room ambient . 清洗后, 样品在室内要单独放置 1 至 2 个小时	Appearance shall no extremely rust. And contacting portions should such that they will work without hindrance for practical. 表面不能有严重的腐蚀, 接触部分要不妨碍正常使用

	Doc. No.	DC Socket-106	Page No.	6/8
	Date Issued	2020-04-06	Prepared by	Shanzha
	Date revised	2024-09-24	checked by	Sangshen
Product Specification	Rev. No.	A1	Approved by	Willy
Title: DC Socket				

7. OTHER PRECAUTIONS 其他注意事项:

- 7.1. Following the soldering process, do not try to clean the switch with a solvent or the like.
进行焊接过程中，不可以用溶剂或类似品清洗开关
- 7.2. Safeguard the switch assembly against flux penetration from its topside.
防止助焊剂从开关的顶端渗入
- 7.3. Please have the products keep in close status and the storage time is 90 days guaranty after delivering the goods at most. 交货后保证开关处于封密状态并库存时间 90 天以下

Rev.	Description	Date revised	Created/ Revised by
A1	New Release	2024/09/24	Sangshen