

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

5025790000

Status:

Active

Overview:

CLIK-Mate Wire-to-Board Connectors

Description:

CLIK-Mate 1.50mm Pitch Crimp Terminal, Male, Tin Plating, 24-28 AWG, Reel



Series image - Reference only

Documents:	
3D Model	Product Specification 5031490000-PS-000 (PDF)
3D Model (PDF)	Product Specification 5031490001-PS-000 (PDF)
Drawing (PDF)	Product Specification 5031491000-PS-000 (PDF)
Product Specification 5025780000-PS-000 (PDF)	Product Specification 5031491001-PS-000 (PDF)
Product Specification 5025780001-PS-000 (PDF)	Product Specification 5031491001-PS-JAP-000 (PDF)
Product Specification 5025780002-PS-000 (PDF)	Product Specification 5031491003-PS-000 (PDF)
Product Specification 5025780003-PS-000 (PDF)	Product Specification 5031491004-PS-000 (PDF)
Product Specification 5025781000-PS-000 (PDF)	Application Specification AS-502578-001-001 (PDF)
Product Specification 5025781000-PS-CHI-000 (PDF)	Application Specification AS-503149-001-001 (PDF)
Product Specification 5025781000-PS-JAP-000 (PDF)	Application Specification AS-503395-001-001 (PDF)
Product Specification 5025781002-PS-000 (PDF)	Packaging Specification SPK-502579-001-001 (PDF)
Product Specification 5025781003-PS-000 (PDF)	RoHS Certificate of Compliance (PDF)

General	
Product Family	Crimp Terminals
Series	130239
Application	Signal, Wire-to-Board
Crimp Quality Equipment	Yes
Overview	CLIK-Mate Wire-to-Board Connectors
Packaging Alternative	5025790100 (Loose)
Product Name	CLIK-Mate
Taxonomy	Crimp Terminals
UPC	800756642857

Physical	
Durability (mating cycles max)	30
Gender	Male
Material - Metal	Copper Alloy
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	42.000/mg
Packaging Type	Reel
Plating min - Mating	0.406µm
Plating min - Termination	0.406µm
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	0.78-1.28mm
Wire Size AWG	24, 26, 28
Wire Size mm²	0.08-0.20

Electrical	
Current - Maximum per Contact	2.0A
Voltage - Maximum	100V AC (RMS)/DC

Material Info

Reference - Drawing Numbers	
Application Specification	AS-502578-001-001, AS-503149-001-001, AS-503395-001-001
Crimp Specification	CS-502579-001-001
Packaging Specification	SPK-502579-001-001
Product Specification	5025780000-PS-000, 5025780001-PS-000, 5025780002-PS-000, 5025780003-PS-000,

EU ELV
Compliant

EU RoHS
Compliant
REACH SVHC

Not Contained per -
D(2022)9120-DC (17
Jan 2023)

Halogen-Free
Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS	Green Image
ELV	Compliant
RoHS Phthalates	Not Contained

Search Parts in this Series
130239 Series

Use With
CLIK-Mate Housing 502578 , 503149

Application Tooling | FAQ
Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global	
Description	Product #
Hand Crimp Tool for 1.50mm Pitch CLIK-Mate Wire-to-Board Crimp Terminals, 24-28 AWG	2002187400
Extractor Tool for 1.50mm Pitch Wire-to-Board Crimp Terminal	638133700
FineAdjust Applicator for 1.50mm Pitch	639025000

Sales Drawing

5025781000-PS-000, 5025781000-PS-CHI-000,
5025781000-PS-JAP-000, 5025781002-PS-000,
5025781003-PS-000, 5031490000-PS-000,
5031490001-PS-000, 5031491000-PS-000,
5031491001-PS-000, 5031491001-PS-JAP-000,
5031491003-PS-000, 5031491004-PS-000
5025790000-SD-000

Wire-to-Board Crimp Terminals T2 Terminator for 1.50mm Pitch Wire- to-Board Terminal Japan	
Description	Product #
S-1 Applicator for CLIK-Mate Plug Terminals, 24-28 AWG	<u>639125000</u> <u>5780473700</u>

This document was generated on 03/23/2023
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION