


39600500440 - 396 Series



Series: 396

 [Fuse 396 Datasheet](#)

Features:

- Lead free
- Reduced PCB space requirements
- Direct solderable or plug-in versions
- Internationally approved
- Low internal resistance
- Shocksafe casing
- Vibration resistance
- Halogen free

Click on part number below for individual TC curve files.

Questions? [Contact Littelfuse Support](#)

 [Check Stock](#)

 [Order Samples](#)



NEW!
Product
Selection
Guide
eCatalog
[Read Now](#)



Electronics
News and Information
[SIGN UP NOW](#)

Feedback

Electrical Characteristics	Technical Resources	Environmental Info
Property (Mouseover for details)	Value	
Ampere Rating (A)	0.05	
Nominal Melting I ² T (A ² sec)	0.0056	
Interrupting Rating	100A@125VAC	
Min Operating Temp °C	-40	
Max Operating Temp (°C)	85	
Moisture Sensitivity Level	MIL-STD-202 Method 106	
Nominal Power Dissipation (W)	45	
Nominal Voltage Drop (mV)	900	
Nominal Cold Resistance (Ohms)	12.5	
Opening	Slo-Blo/Time Lag (T)/Time Delay	
Package Size	TE5 (8.5x8mm)	
VAC (V)	125	

Connect with Littelfuse

Sign up to receive special offers and news

Enter your email

Submit

For more details about how we use your information, check our [Privacy Statement](#).



 [Mobile Site](#)

About Littelfuse

- About Littelfuse
- Conflict Free Statement
- History
- Investor Relations
- Legal
- Press Room
- Privacy Statement
- Supply Chain Transparency
- Website Feedback

Explore Littelfuse

- Capabilities Brochures
- Careers
- Check Distributor Stock
- Competitor Cross Reference
- Industries
- Order Samples
- Products
- Services

Technical Resources

- Application Designs
- Education
- FAQs
- iDesign™
- Littelfuse University
- Product Catalogs
- Quality Documents
- Technical Documents