

# Power Cords & Plugs - Cords



## 3 Conductor - Plastic - Detachable - Unshielded and Shielded cont.

NEMA 5-15P pin. One end molded PVC grounding plug PH-290D. Other end molded PVC right angle grounding connector PH-910 IEC 320-C13.



Temperature rating is 60°C. Color coding is for international. Jacket color is black.

## 3 Conductor - Plastic - Detachable - Special Use

### Detachable with Full Mounting Ears - Unshielded


NEMA 5-15P pin. One end molded PVC grounding plug PH-290B. Other end molded PVC grounding connector PH-386G IEC 320-C13. Temperature rating is 60°C. Color coding is for international. AWG stranding is 18 (41 x 34) Rating is 1250 watts 10A-125V. Cord type is SVT. Jacket color is black.



Part #	Lgth ft (m)	Pkg-Units per Ctn	Nominal O.D. inch (mm)
17550	6'7" (2)	H-100, H-25	.246 (6.25)
17734	6'7" (2)	H-25	.253 (6.43)

## Y-Cords

One end molded PVC grounding AEC-150 IEC 320 C14. ( Part numbers 17272A, 17273A, 17274A and 17275A grounding plug is AEC-30.) Other end molded PVC grounding connector AEC 250A IEC 320



C13. Temperature rating is 60°C. Packaging - units per carton are B-25. Color coding is for North American. Cord type is SJT. Jacket color is black.

Part #	Length	AWG Stranding	Nominal O.D. inch (mm)	Rating
17268A	6' overall, 2' legs	18 (41 x 34)	.315 (8.00)	1250 watts 10A-125V
17269A	10' overall, 2' legs	18 (41 x 34)	.315 (8.00)	1250 watts 10A-125V
17270A	6' overall, 2' legs	16 (65 x 34)	.340 (8.00)	3250 watts 13A-250V
17271A	10' overall 2' legs	16 (65 x 34)	.340 (8.00)	3250 watts 13A-250V
17272A	6' overall, 2' legs	18 (41 x 34)	.315 (8.00)	1250 watts 10A-125V
17273A	10' overall, 2' legs	18 (41 x 34)	.315 (8.00)	1250 watts 10A-125V
17274A	6' overall, 2' legs	16 (65 x 34)	.340 (8.00)	3250 watts 13A-250V
17275A	10' overall, 2' legs	16 (65 x 34)	.340 (8.00)	3250 watts 13A-250V



## Appliance and Electronic Cords

### Appliance Type Cord

NEMA 1-15P pin. One end is non-polarized molded plug AEC-22R. Other end conductors split 1 1/2" (38mm) stripped and twisted 1/2". Temperature rating is 60°C. Color coding is for North American. AWG stranding is 18 (41 x 34). Rating is 1250 watts 10A-125V.



Part #	Lgth ft (m)	Pkg-Units per Ctn	Nominal O.D. inch (mm)	Cord Type	Jacket Type
17503A	6 (1.83)	H-50	.106 x .208 (2.69 x 5.28)	SPT-1	Black

### Appliance Type Cord

NEMA 1-15P pin. One end is non-polarized molded PVC cord-holder plug PH-289-SN-G. Other end outer jacket stripped 1 1/2" (38mm), conductors stripped and twisted 5/8" (16mm). For food mixers, blenders and small appliances. Temperature rating is 60°C. Color coding is for North American. AWG stranding is 18 (41 x 34). Rating is 1250 watts 10A-125V.



Part #	Lgth ft (m)	Pkg-Units per Ctn	Nominal O.D. inch (mm)	Cord Type	Jacket Type
17205	6 (1.83)	B-50	.243 (6.17)	SVT	Black, gray

### SPT Parallel Cords

NEMA 1-15P pin. One end has polarized molded PVC plug, PH-S 289-S. Other end has conductors split 1 5/8" (41.28mm), stripped and twisted 5/8" (16mm). Temperature ratings is 60°C. Color coding is ribbed neutral. AWG stranding is 18 (41 x 34). Nominal O.D. is .110 x .220 (2.79 x 5.59). Rating is 1250 watts 10A-125V. Cord type is SPT-1. For radios, desk fans and small appliances. Long life plastic resists cracking and aging.



Part #	Lgth ft (m)	Pkg-Units per Ctn	Jacket Color
17109	9 (2.74)	B-50, S-25 (available in brown only)	Brown, white
40112	12 (3.66)	H-50	Brown, white

### SPT Parallel Cords

NEMA 1-15P pin. One end is molded PVC plug PH-S298SN. Other end molded PVC round pin connector PH-98A. Fits latest hand held food mixer models such as Dormeyer, G.E., Hamilton Beach, Sunbeam and Westinghouse. Temperature rating is 60°C. Packaging - units per carton are H-50. AWG stranding is 18 (41 x 34). Cord type is SPT-2.



Part #	Lgth ft (m)	Nominal O.D. inch (mm)	Rating	Jacket Color
40186	6 (1.83)	.144 x .277 (3.66 x 7.04)	875 watts 7A-125V	White

### SPT Parallel Cords

NEMA 5-15P pin. One end molded PVC plug AEC-30. Other end conductors split 2" (51mm), stripped and twisted 1/2" (12.7mm). Temperature rating is 60°C. Packaging - units per carton are H-50. Color coding is North American. AWG stranding is 18 (41 x 34). Cord type is SPT-2.



Part #	Lgth ft (m)	Nominal O.D. inch (mm)	Rating	Jacket Color
17504A	6 (1.83)	.175 x .385 (4.45 x 9.78)	1250 watts 10A-125V	Black