



Part Number : [903270306](#)

Product Description : Picoflex PF-50, Low Profile, IDT Receptacle, 6 Circuits, White, Tin (Sn) Plated, Bag

Series Number : 90327

Status : Active

Product Category : Connector Housings



Documents & Resources

Drawings

[Drawing 903270306_sd.pdf](#)

3D Models and Design Files

[3D Model 903270306_stp.zip](#)

[3D Model PDF 903270306.pdf](#)

Specifications


[Application Specification 908140000-AS-000.pdf](#)

[Packaging Specification PK-90327-001-001.pdf](#)

[Product Specification PS-99020-0011-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 44
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

[Multiple Part Product Compliance Statements](#)

- Eu RoHS
- REACH SVHC
- Low-Halogen

[Multiple Part Industry Compliance Documents](#)

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Connector Housings
Series	90327
Description	Picoflex PF-50, Low Profile, IDT Receptacle, 6 Circuits, White, Tin (Sn) Plated, Bag
Comments	Low Profile
Component Type	Housing
Product Family	Picoflex Ribbon-Cable Connectors
Product Name	Picoflex
UPC	800753538115

Agency

CSA	LR19980
UL	E29179

Electrical

Current - Maximum per Contact	1.2A
Voltage - Maximum	250V

Physical

Circuits (Loaded)	6
Circuits (maximum)	6
Color - Resin	White
Durability (mating cycles max)	30
Entry Angle	Vertical
Flammability	94V-0

Gender	Receptacle
Glow-Wire Capable	No
Lock to Mating Part	Yes
Material - Metal	Phosphor Bronze
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Material - Resin	Polyester
Net Weight	0.399/g
Number of Rows	2
Packaging Type	Bag
PCB Locator	No
PCB Retention	None
Pitch - Mating Interface	1.27mm
Pitch - Termination Interface	1.27mm
Polarized to Mating Part	Yes
Polarized to PCB	No
Shrouded	Fully
Stackable	No
Temperature Range - Operating	-40° to +105°C
Termination Interface Style	IDT or Pierce
Wire/Cable Type	Ribbon Cable
Wire Insulation Diameter	1.00mm max.
Wire Size (AWG)	26, 28

Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

Mates With / Use With

Mates with Part(s)

Description	Part Number
Picoflex PF-50 Vertical Low Profile Headers	<u>90325</u>
Picoflex PF-50 Vertical Low Profile Headers	<u>90779</u>

Picoflex PF-50 Vertical Surface Mount Headers	<u>90814</u>
---	--------------

Application Tooling

Global

Description	Part Number
Extractor Tool for Connectors	<u>0621006000</u>
Extraction Tool for Picoflex PF-50 Connectors, 4-26 Circuits	<u>0690081070</u>
Extraction Tool (Steel) for 4-26 Circuit	<u>0690081071</u>
Parallel Action Handtool for 4-26 Circuit	<u>0690081080</u>
PremiumGrade Hand Crimp Tool for Picoflex PF-50 IDT Receptacle, 4-26 Circuits, 26 or 28 AWG Flat Cable, 1.00mm max. Thickness	<u>0690081090</u>
Arbor Press Fixture	<u>0690201902</u>
Arbor Press Fixture	<u>0690201908</u>
Semi-Automatic Bench Press PB14 for 4-26 Circuit	<u>0691271001</u>
Semi-Automatic PB14 Bench Press with Auto De-reeling	<u>0691271004</u>
Semi-Automatic Bench Press PB14 WG	<u>0691271037</u>
Assembly of De-Tape Unit for Semi-Automatic Bench Press PB14	<u>0691275045</u>

This document was generated on Sep 04, 2023