


Honeywell Sensing and Control

Order Product and **Get Support**

- U.S. Authorized **Distributors**
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

Home> Products > MICRO SWITCH™ Sealed and High Accuracy Switches > AT > Product Page

64AT22-7



AT Series Toggle Switch, 4 pole, 3 position, Quick Connect terminal, **Standard Lever**

My Links

Login to iCOM Login as Rep/AD

Login as Guest

Login to Digital University

Search for product and

All Sensing and Contro

support information.

Keyword Search

Product Search

Part number search:

Use (*) to expand search

Specification Search

Actual product appearance may vary.

Features

Gold or silver contacts Choice of sealed bushing Standard or pull to unlock toggle lever Short behind-panel depth Solder or quick connect termination 2,4, 6, or 8 SPDT precision basic switches

2 or 3 position, momentary or maintained action

Industrial machinery and equipment Military and commercial aviation Construction equipment Test instruments Agricultural machinery Process control

Potential Applications

Medical instrumentation

Description

Compact multipole 2, 4, 6,or 8 SPDT design. MICRO SWITCH™ precision basic switches conserve space and weight. Pull -to-Unlock Toggle Levers prevent accidental operation: the lever must be pulled approximately 2,3 mm [0.09 inches] to change the positions. Many locking configurations are available. Lever to bushing seals. Hermetic basic switches are available. AT qualified versions meet MILS-8805/98. Various levers and styles are available.


Supporting Documentation

Accessory: Lever Sleeve

Panel Cutout Engineering

Accessory: Seals

Accessory: Nuts



Terms & Conditions | Privacy Statement |