

Garant**Dial indicator shock-resistant, Measuring range / Body Ø: 10/58mm****Order data**

Order number	432110 10/58
GTIN	4045197154064
Item class	41C

Description**Version:**

Dimensions to DIN EN ISO 463, issue June 2006. **Shock-resistant** precision dial indicators. Clamping shank Ø 8 mm h6, hardened and ground. Outer ring of dial face can be rotated to zero the dial. Outer ring with 2 adjustable tolerance pointers. Central pointer for 1/100 mm reading, small pointer on sub-scale for 1 mm reading.

Protected against shocks to the gears. With metal outer ring and metal back.

Shocks are not transmitted directly to the mechanism. Particularly strong and tough.

Version of the advertising text:

Shock-resistant precision dial indicators. Clamping shank Ø 8 mm h6, hardened and ground. Outer ring of dial face can be rotated to zero the dial. Outer ring with 2 adjustable tolerance pointers. Central pointer for 1/100 mm reading, small pointer on sub-scale for 1 mm reading.

Optional extras:

Special contact points No. 434900; 434910; 434915.

Technical description

Gauging force	0.7 - 1.5 N
Graduation	0.01 mm

Calibration	C1
Reading per pointer revolution	1 mm
Measuring range	10 mm
Body Ø	58 mm
Standard	DIN 878
Measurement variation MPE (measurement range)	15 µm
Rotatable dial face	yes
adjustable tolerance marks	yes
Measurement technology	analogue
Packaging	sturdy box
Type of product	dial gauge

Suitable products

<https://www.hoffmann-group.com/GB/en/hom/p/432110-10/58>