

This document was generated on 03/11/2023 -

<u>638131400</u>

AWG

Terminals

Extraction Tool for

SPOX, MX64, Ditto, MX150CE, Milli-Grid

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION				
Part Number: Status: Overview: Description:	0503948051 Active Milli-Grid Connector S 2.00mm Pitch, Milli-G	S <u>ystem</u> rid Female Crimp Terminal, 0.38µm Select Gold, Reel, Lead free		
Documents: <u>3D Model</u> <u>Drawing (PDF)</u> <u>3D Model (PDF)</u> <u>Product Specification</u>	on PS-51110-001-001 (PE	Packaging Specification 503940001-000 (PDF) Product Guide (PDF) RoHS Certificate of Compliance (PDF) PF)	- Series ima	ge - Reference only
General Product Family Series Application		Crimp Terminals <u>50394</u> Signal, Wire-to-Board, Wire-to-Wire	EU ELV Compliant	
Crimp Quality Equip Overview Packaging Alternati Product Name Taxonomy UPC		Yes <u>Milli-Grid Connector System</u> <u>503948100</u> (Loose) Milli-Grid Crimp Terminals 800753576193	EU RoHS Compliant REACH SVHC Not Contained per D(2022)9120-DC Jan 2023) Halogen-Free	
Physical Durability (mating c Gender Material - Metal Material - Plating M Material - Plating Te Net Weight Packaging Type	ating	50 Female Copper Alloy Gold Nickel 43.000/mg Reel	Status Low-Halogen	ion, please visit <u>Contact US</u> Green Image Compliant Not Contained
Plating min - Mating Plating min - Termination Termination Interface: Style Wire Insulation Diameter		0.381µm 2.000µm Crimp or Compression 1.40mm max.	Search Parts in this Series 50394 Series	
Wire Size AWG Wire Size mm ²		24, 26, 28, 30 N/A	Use With Milli-Grid Recep <u>151100</u> , <u>15119</u>	tacle Housing <u>51110</u> , <u>2</u>
Current - Maximum per Contact Voltage - Maximum		2.0A 125V AC (RMS)/DC	Application Tooling <u>FAQ</u> Tooling specifications and manuals are	
Solder Process Data Lead-freeProcess Capability Material Info		N/A	found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling	
Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing		503940001-000 PS-51110-001-001 CS-50394-001, SD-50394-8XXX-000	Specification document. Global Description Product # Hand Crimp Tool 2133091200 for Milli-Grid and MicroBlade Crimp Terminals, 24-30 AWG	

FineAdjust Applicator639005200 for 2.00mm Pitch Wire-to-Board Crimp Terminals, 24-30 AWG Wire, Insulation OD 1.10-1.30mm FineAdjust Applicator 639046800 for 2.00mm Pitch Wire-to-Board Crimp Terminal, 24-30 AWG, Insulation OD 0.90-1.10mm T2 Terminator Die 639105200 Japan Description Product # S-1 Applicator for 573153700 Milli-Grid Receptacle Terminal, 24-30 AWG

This document was generated on 03/11/2023 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION