

Quick Links

Cross reference

RoHS/LF P/N Search

Industry Standards

Alphabetical List

Documentation

3D model search

Customer drawing search


Multi Selection Search

Search by category

Start > Search=10129381-906001BLF* > 10129381-906001BLF

10129381-906001BLF

10129381-906001BLF - EconoStik™ : Unshrouded Header, Double Row, Vertical, Through Hole, 6 Positions, 2.54 mm Pitch, 5.84 mm (0.23 in.) Mating, 3.05 mm (0.12 in.) Tail



ACTIVE

RoHS Compliant

Distributor Stock

Print Datasheet

FCI Brings You More

Contact our sales/technical support

Sample request

Customer drawing

Product Environmental Compliance Report

Specifications

Download document

Mating Half

General Dimensional Electrical Mechanical Physical Approvals / Certifications Mounting	
General	
Number of contacts (per row)	3
Number of contacts (Total)	6
Number of rows	2
Orientation	Vertical
Packaging	Bulk Packaging
Attachment type (Board)	Through Hole
Series Number	10129381
Dimensional	
Length (Mating pin)	5.84 mm (0.23 in.)
Length (Overall pin)	11.43 mm (0.45 in.)
Length (Tail)	3.05 mm (0.12 in.)
Electrical	
Current rating	3 amp Continuous
Resistance (Insulation)	1000 M-ohms
Voltage rating	1500V AC rms
Mechanical	
Retention force	9N
Physical	
Color (Housing)	Black
Material (Contact)	Brass
Material (Housing)	High Temperature Black Thermoplastic
Plating (Contact area)	0.025 µm (1 µin.) Gold
Plating (Tail)	0.025 µm (1 µin.) Gold
Underplating (Contact)	1.27 µm (50 µin.) Nickel
Flammability rating	UL 94 V-0
Temperature (Range)	-55°C to +105°C
Approvals / Certifications	
Approvals / Certifications	UL and CSA Approved
CSA File Number	LR46923
UL File Number	E66906
Mounting	
Retention feature (Board)	No
Solder process	Vapor-phase IR Reflow Soldering Processes Compatible with Wave

Disclaimer : The information above is for reference only. For more technical details, refer to product specification and application specification.