




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.82 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Steel
Terminal Plating Material	Nickel
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.41 mm[.016 in]
Product Length	19.18 mm[.755 in]
Compatible Insulation Diameter Range	1.52 – 2.8 mm[.06 – .11 in]
Wire Size	.82 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 250 °C[-40 – 482 °F]

Industry Standards

Agency/Standard	CSA, UL
-----------------	---------

Packaging Features

Packaging Quantity	11000
Packaging Method	Strip/Reel

Other

Line	Premier
------	---------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>




EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability




Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 63892-1 250 FASTON REC 16-12 AWG NPST	 TE Part # 2-2150551-1 OCEAN_2.0_Applicator-E-110F1200	 TE Part # 2-2150551-2 OCEAN_2.0_Applicator-E-110F1200A	 TE Part # 2150551-1 OCEAN_2.0_Applicator-E-110F1200
 TE Part # 2150551-2 OCEAN_2.0_Applicator-E-110F1200A	 TE Part # 7-2150551-1 OCEAN_2.0_Applicator-E-110F1200	 TE Part # 7-2150551-2 OCEAN_2.0_Applicator-E-110F1200A	 TE Part # 7-2150551-7 OCEAN_2.0_SPARE_PART_KIT-110F1200

Also in the Series | FASTON 250

 Compression Connectors(4)	 Crimp Terminal Housings(142)	 Insertion & Extraction Tools(6)	 Magnet Wire Terminals(1)
--	---	--	---



PCB Terminals(135)



Quick Disconnects(445)



Splices(4)

Customers Also Bought



TE Part #5413879-1
JACK ASSY,RTANG,BNC



TE Part #5750071-1
Mini DIN, 6 pos, R/A, Shield



TE Part #34147
PG R 22-16 COMM 22-18 MIL 6



TE Part #2227303-1
CAGE ASSEMBLY, SFP, .140 SOLDE



TE Part #1217345-1
110 FASTON,REC.,16-18 AWG,BR




TE Part #796859-2
2 POS TERMI-BLOK PLUG RT ANGLE



TE Part #1-350715-1
06P UMNL V0 PLUG HSG BROWN



TE Part #3-644860-6
06P MTA156 CONN ASSY 18AWG LF



TE Part #520936-1
POWER RING 250 ASY 16-10 AWG NL



TE Part #2232327-2
CLUSTER BLOCK HSG .090 DIA

Documents

Product Drawings

250 FASTON REC 18-14 AWG NPST

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_63688-1_G.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_63688-1_G.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_63688-1_G.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[82004 FASTON Terminals \(Insulated and Uninsulated\) Catalog - FASTON Receptacles Section](#)

English

Product Specifications

[Application Specification](#)

English

Product Environmental Compliance

[MD_63688-1_111620181055_dmtec](#)

English

[MD_63688-1_111620181055_dmtec](#)

English

Agency Approvals

[Agency Approval Document](#)

English