

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

,1998

© COPYRIGHT 1998

BY AMP INCORPORATED. ALL RIGHTS RESERVED.

LOC
J

DIST

REVISIONS

P	LTR	DESCRIPTION	ECN	DATE	DWN	APVD
0		RELEASED	FJ00-1755-99	28FEB'00	K.I.	I.H.
A		REVISED	FJ00-1080-00	21SEP'00	Y.K.	S.M.
B		REVISED	FJ00-2536-02	5DEC'02	T.S.	S.M.
C		REVISED	FJD0-0039-03	6/2 '03	T.S.	S.M.

デートコード

DATE CODE

回路番号
CIRCUIT NO

シリーズマーク
SERIES MARKAMP マーク
AMP MARK

NOTES

1. MATERIAL: HOUSING: GLASS FILLED THERMO PLASTIC
POLYESTER(94V-0), COLOR: BLACK

TAB CONTACT: COPPER ALLOY

RETENTION LEG: BRASS

△ FINISH (CONTACT AREA): 0.38μm MIN GOLD PLATING
OVER NI PLATING△ FINISH (RETENTION LEG): TIN PLATED
(CONTACT TAIL) OVER NICKEL

推奨基板取付け寸法(公差: ±0.05)

PC 基板厚: 1.6±0.3
(コネクタ搭載面)

RECOMENDED PC BOARD HOLE PATTERN (TOL: ±0.05)

PC BOARD THICKNESS: 1.6±0.3
(CONNECTOR MOUNT SIDE)

注記

1. 材料: ハウジング: ガラス入り熱可塑性

ポリエステル樹脂 (94V-0), 色: 黒

タブ コンタクト: 銅合金

リテンション レグ: 黄銅

△ めっき: コンタクト: 全面Ni下地
接触部: 0.38μm MIN金めっき△ めっき: リテンションレグとコンタクト半田付部
: ニッケル下地の上にスズめっき

1376135-2
(KEYING Y)
SCALE: 2-1

1376135-3
(KEYING Z)
SCALE: 2-1THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED.
IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING
ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.DWN 24/FEB/'00
K.IKEDACHK 28/FEB/'00
Y.KATOAPVD 28/FEB/'00
I.HASEGAWAPRODUCT SPEC
製品規格

108-5619

APPLICATION SPEC
取付適用規格

114-5258

WEIGHT

DIMENSIONS:
単位 形
mmTOLERANCES UNLESS
OTHERWISE SPECIFIED一般公差
1φ : ±0.3
3φ : >10 : ±0.35
10φ : >30 : ±0.4
ANGLE : ±3°MATERIAL
材料 注記参照
SEE NOTESFINISH
仕上 注記参照
SEE NOTES

CUSTOMER DRAWING

tyco
ElectronicsTyco Electronics AMP K.K.
Kawasaki, JapanNAME
名称 1列 ヘッダーアセンブリー 3P
(水平タイプ)
SINGLE ROW HEADER ASS'Y 3P ("H"TYPE)
<DYNAMIC D-2100S>SIZE CAGE CODE DRAWING NO
A3 00779 1376135

RESTRICTED TO

SCALE 4-1 SHEET 1 OF 1 REV C

AMP14-70-19 REV 10/93

(CUSTOMER DRAWING) 顧客用図面

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1376135-2](#)