

[Find by Feature](#)
[Browse by Category](#)
[Share](#)
 Search →

Enter part number or keyword

Search Results (129)

[Search Options](#)

129 Results:

1 2 3 4

[Compare](#)

**12047767 Female Metri-Pack 150 Tin Plated Terminal, Cable range 0.80 - 1.00 mm<sup>2</sup>**


[12047767 FLRY-B 0,75 to 1,0 S](#)


[12047767 FLU142Y 0,75 to 1,0 S](#)
[10719093 ASM CONN 2 F M/P 150 BLK SLD](#)
[10718786 CONN 2 F M/P 150 NAT SLD](#)
[10721222 CONN 2 F M/P 150 GRA SLD](#)
[12045895 CONN 4 F M/P 150 280 SLD](#)
[12047867 CONN 4 F M/P 150 BLK](#)
[12059555 CONN 4 F M/P 150 GRA MD](#)
[12064843 CONN 26 F M/P 150 280](#)
[Compare](#)

1 2 3 4

Keyword: 12047767

[Edit Search Options](#)

## Female Metri-Pack 150 Tin Plated Terminal, Cable range 0.80 - 1.00 mm<sup>2</sup> Part #12047767


[Attributes](#)
[Documents \(10\)](#)

|                                                           |                                                                                    |
|-----------------------------------------------------------|------------------------------------------------------------------------------------|
| <b>Part #:</b>                                            | 12047767                                                                           |
| <b>Description:</b>                                       | Female Metri-Pack 150 Tin Plated Terminal, Cable range 0.80 - 1.00 mm <sup>2</sup> |
| <b>Product Type:</b>                                      | Terminal                                                                           |
| <b>Status:</b>                                            | Active                                                                             |
| <b>Blade size [mm]:</b>                                   | 1.5                                                                                |
| <b>Terminal family:</b>                                   | Metri-Pack                                                                         |
| <b>Series:</b>                                            | 150                                                                                |
| <b>Gender:</b>                                            | Female                                                                             |
| <b>Sealed:</b>                                            | Unsealed                                                                           |
| <b>Plating:</b>                                           | Tin                                                                                |
| <b>Minimum Cable Core Cross Section [mm<sup>2</sup>]:</b> | 0.80                                                                               |
| <b>Maximum Cable Core Cross Section [mm<sup>2</sup>]:</b> | 1.00                                                                               |
| <b>Minimum Cable Diameter [mm]:</b>                       | 1.70                                                                               |
| <b>Maximum Cable Diameter [mm]:</b>                       | 2.40                                                                               |
| <b>Current range [A]:</b>                                 | 14                                                                                 |
| <b>Temperature range [ ]:</b>                             | -40 to 125                                                                         |

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.