



P-DUKE POWER

TAD100 Series

2 X 3 Inch AC-DC POWER SUPPLIES
Up to 100 Watts

3
YEARS
WARRANTY

ROHS
COMPLIANT

REACH
COMPLIANT

+85°C
-40°C
AMBIENT TEMP.



Automation



Datacom



IPC



Industry



Measurement



Telecom



Automobile



Boat



Charger



Medical



PV



Railway

UL US CB CE UK CA



3000 VAC
Reinforced Insulation

ADJ.
Output Voltage

Internal EN55032
Class **B**

LOW
Leakage Current

LOW
Standby Power

Protection Class I
Class II

Operating Altitude
5000
meter

OCP

OVP

SCP

PART NUMBER STRUCTURE

T	A	D	100	U	S	12	B	-			
Application	Package Code	Dimension Code	Output Power (W)	Input Voltage (VAC)	Output Quantity	Output Voltage (VDC)	Protection Type		Connector Options	Application Options	Conformal Coating Options
Industry Application	A: Open type U: U chassis type E: Enclosed type D: Din rail type			U: Universal 85 ~ 264	S: Single	12: 12 15: 15 24: 24 28: 28 36: 36 48: 48	B: CLASS II □: CLASS I		□: JST M: Molex T: Terminal Block	□: None C: OVC III□	□: None R: Conformal Coating

TECHNICAL SPECIFICATION All specifications are typical at 230VAC input, full load and 25°C unless otherwise noted

Model Number	Input Range	Output Voltage	Output Current Natural Convection	Input Power No Load	Efficiency	Maximum Capacitor Load
	VAC	VDC	A	W	%	μF
TAD100US12B	85 ~ 264	12	8.34	0.3	91	6950
TUD100US12B						
TED100US12B						
TDD100US12B						
TAD100US15B	85 ~ 264	15	6.67	0.3	92	4450
TUD100US15B						
TED100US15B						
TDD100US15B						
TAD100US24B	85 ~ 264	24	4.17	0.3	92	1750
TUD100US24B						
TED100US24B						
TDD100US24B						
TAD100US28B	85 ~ 264	28	3.58	0.3	92	1280
TUD100US28B						
TED100US28B						
TDD100US28B						
TAD100US36B	85 ~ 264	36	2.78	0.3	91	770
TUD100US36B						
TED100US36B						
TDD100US36B						
TAD100US48B	85 ~ 264	48	2.09	0.3	91	430
TUD100US48B						
TED100US48B						
TDD100US48B						

INPUT SPECIFICATIONS						
Parameter	Conditions	Min.	Typ.	Max.	Unit	
Operating input voltage range	AC input	85		264	VAC	
	DC input	120		370	VDC	
Input frequency	AC input	47		63	Hz	
Input current	115VAC and Full Load			1.15	A	
	230VAC and Full Load			0.55		
No load input power	230VAC			0.3	Watts	
Leakage current	264VAC			300	μA	
Power Factor		0.95				
Start up time				1000	ms	
Rise time			20		ms	
Hold up time	115VAC and Full Load	22			ms	
Input inrush current	230VAC			100	A	
Input protection	Internal fuse			T3.15A/250VAC		

OUTPUT SPECIFICATIONS

Parameter	Conditions	Min.	Typ.	Max.	Unit
Output power				100	Watts
Initial set voltage accuracy	230VAC and Full Load	-1.0		+1.0	%
Line regulation	Low Line to High Line at Full Load	-0.2		+0.2	%
Load regulation	No Load to Full Load 10% Load to 90% Load	-0.5 -0.4		+0.5 +0.4	%
Voltage adjustability		-10		+10	%
Minimum load			0		%
Ripple and noise	Measured by 20MHz bandwidth With a 10 μ F/25V 1206 X7R MLCC 12Vout 15Vout With a 1 μ F/50V 1206 X7R MLCC 24Vout 28Vout 36Vout With a 0.1 μ F/100V 1206 X7R MLCC 48Vout		120 150 160 180 190 340		mVp-p
Temperature coefficient		-0.02		+0.02	%/°C
Transient response	Load step from 50 ~ 75% change at 2.5A/ μ s Peak deviation Recovery time		500	3	% Vout μ s
Over voltage protection	% of Vout(nom); Latch mode	115		135	%
Over load protection	% of Iout rated; Hiccup mode	115		150	%
Short circuit protection		Continuous, automatic recovery			

GENERAL SPECIFICATIONS

Parameter	Conditions	Min.	Typ.	Max.	Unit
Isolation voltage	1 minute (Reinforced insulation) Input to Output Input (Output) to F.G.	3000 1500			VAC
Isolation resistance	500VDC	0.1			G Ω
Switching frequency			60		kHz
Safety approvals	IEC/ EN/ UL 62368-1 (OVC III)			UL:E193009 CB:UL(Demko)	
Weight	TAD TUD TED TDD			156g (5.50oz) 194g (6.84oz) 210g (7.41oz) 232g (8.18oz)	
MTBF	MIL-HDBK-217F Ta=25°C, Full load			7.903 x 10 ⁵	hrs


ENVIRONMENTAL SPECIFICATIONS

Parameter	Conditions	Min.	Typ.	Max.	Unit
Operating ambient temperature	Natural convection and Full load (with derating) -40°C start up : 80% Load,max. @ Vin > 100VAC -40°C start up : 100% Load,max. @ Vin > 200VAC	-40		+85	°C
Storage temperature range		-40		+85	°C
Operating altitude				5000	m
Shock				IEC60068-2-27	
Vibration				IEC60068-2-6	
Relative humidity	Non-condensing			5% to 95% RH	


EMC SPECIFICATIONS

Parameter	Conditions	Level
EMI	EN55032 and FCC Part 15 External components may be required for class I application.	Conducted ClassB Radiated ClassA
Harmonic currents	EN61000-3-2 Full Load	Class A and D
Voltage flicker	EN61000-3-3	
EMS	EN55035	
ESD	EN61000-4-2	Perf. Criteria A
Radiated immunity	EN61000-4-3 20 V/m	Perf. Criteria A
Fast transient	EN61000-4-4 $\pm 2\text{kV}$	Perf. Criteria A
Surge	EN61000-4-5 DM $\pm 1\text{kV}$ and CM $\pm 2\text{kV}$	Perf. Criteria A
Conducted immunity	EN61000-4-6 20 Vr.m.s	Perf. Criteria A
Power frequency magnetic field	EN61000-4-8 10 A/m	Perf. Criteria A
Dip and interruptions	EN61000-4-11	


CHARACTERISTIC CURVE




TED100 & TDD100 Derating Curve vs. Ambient Temperature




TAD100 & TUD100 Derating Curve vs. Ambient Temperature



TD100 Derating Curve vs. Input Voltage




TD100US24B Efficiency vs. Output Load



TD100US24B Efficiency vs. Input Voltage

MECHANICAL DRAWING

TAD Open type




1. All dimensions in inch [mm]
Tolerance : $x.xx \pm 0.02$ [$x.x \pm 0.5$] $x.xxx \pm 0.01$ [$x.xx \pm 0.25$]
2. The screw locked torque: MAX 3.4kgf-cm/0.33N-m

CONNECTORS CONNECTIONS

CON1 – Input Connector

Pin 1	Line
Pin 3	Neutral

TDD Din rail type



1. All dimensions in inch [mm]
Tolerance : $x.xx \pm 0.02$ [$x.x \pm 0.5$] $x.xxx \pm 0.01$ [$x.xx \pm 0.25$]


CON2 – Output Connector

Pin 1,2	-Vout
Pin 3,4	+Vout

*Either one of four screws holes of Open / Chassis type can be considered as PE connection for CLASS I application.

MECHANICAL DRAWING(CONTINUED)


TED Enclosed type



BOTTOM VIEW

1. All dimensions in inch [mm]
Tolerance : x.xx±0.02 [x.x±0.5] x.xxx±0.01 [x.xx±0.25]
2. The screw locked torque: MAX 4.2kgf-cm/0.41N-m

TUD U chassis type



BOTTOM VIEW

1. All dimensions in inch [mm]
Tolerance : x.xx±0.02 [x.x±0.5] x.xxx±0.01 [x.xx±0.25]
2. The screw locked torque: MAX 4.2kgf-cm/0.41N-m

CONNECTORS CONNECTIONS

CON1 – Input Connector

Pin 1	Line
Pin 3	Neutral

CON2 – Output Connector

Pin 1,2	-Vout
Pin 3,4	+Vout

*Either one of four screws holes of Open / Chassis type can be considered as PE connection for CLASS I application.

CONNECTOR OPTIONS

Blank:

JST Type

Mates with housing

CON1: **VHR-3N**

CON2: **VHR-4N**

Crimp terminals

CON1: **SVH-21T-P1.1**

CON2: **SVH-21T-P1.1**



-M

Molex Type

Mates with housing

CON1: **09-50-8031**

CON2: **09-50-8041**

Crimp terminals

CON1: **SD-2478**

CON2: **SD-2478**



-T

Terminal Block

**Screw locked torque
MAX 2Kgf.cm/0.2N.m**

**Wire dimension range
26 ~ 16AWG**

