



Holder / No. 562 PC Mount, for TR5®/TE5® Fuses



Holes in PCB



Specifications

- Packaging**
100 bulk (1000 pcs.)
- Mounting**
PC Board, 5.08mm pin spacing
- Materials**
Holder: Black Thermoplastic, UL94 V-0
 Nylon 46
Terminals: Copper alloy; solderable
 tinned
- Electrical Data (23°C)**
Rated Voltage: 250V
Max. Current/Power: 6.3A/1.6W
- Minimum Cross Section**
Conducting path - 0.1mm²
- Unit Weight**
0.12g




Order Information


Qty.	Order-Number	Series	Packaging
		562	0000
			100

Specifications are subject to change without notice

Holder / No. 564 Surface Mount, for TR5®/TE5® Fuses



recommended Pad Layout (mm)



- Packaging**
100 Tape/Reel (1500 pcs.)
 Carrier tape width 16 mm
 Reel diameter 33 cm
- Order Number**
Holder No. 564 0000 100
- Mounting**
PC Board, 5.08mm pad spacing
- Materials**
Holder: Black Thermoplastic, UL94 V-0
 Nylon 46
Terminals: Copper alloy; solderable
 tinned
- Electrical Data (23°C)**
Rated Voltage: 250V
Max. Current/Power: 6.3A/1.6W
- Minimum Cross Section**
Conducting path - 0.1mm²
- Unit Weight**
0.44g



Order Information

Qty.	Order-Number	Series	Packaging
		564	0000
			100

Specifications are subject to change without notice

Note: 1.00 means the number one with two decimal places. 1,000 means the number one thousand.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Littelfuse:](#)

[56400001009](#) [56200001009](#)