




MATE-N-LOK | Universal MATE-N-LOK

TE Internal #: 640466-1
Rectangular Power Connectors, Header, Plug, Wire-to-Board, 5
Position, 6.35 mm [.25 in] Centerline, Printed Circuit Board,
Universal MATE-N-LOK

[View on TE.com >](#)

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**
Connector & Housing Type: **Plug**
Connector System: **Wire-to-Board**
Number of Positions: **5**
Centerline (Pitch): **6.35 mm [.25 in]**

Features

Product Type Features

Rectangular Power Connector Type	Header
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	5
PCB Mount Orientation	Vertical
Number of Power Positions	5
Number of Rows	1

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

Multiple Contact Types	Without
------------------------	---------



Contact Layout	Inline
Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	12 A
Contact Retention Within Housing	Without
Contact Type	Pin
PCB Contact Termination Area Plating Material	Pre-Tin
Contact Mating Area Plating Material Thickness	3.81 – 5.08 µm[150 – 200 µin]

Termination Features

Termination Post & Tail Length	3.56 mm[.14 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

Strain Relief	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention Type	Positive Lock
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	6.35 mm[.25 in]
Housing Color	Natural
Housing Material	Nylon

Dimensions

Connector Height	7.62 mm
PCB Thickness (Recommended)	1.6 mm[.063 in]
Product Width	13.97 mm
Product Length	33.02 mm

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Operation/Application



Circuit Application	Power
---------------------	-------

Industry Standards

CSA Rating	Certified, LR 7189
UL Rating	Recognized
Agency/Standard	CSA, UL, VDE
Approved Standards	UL E28476
UL Flammability Rating	UL 94V-2
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Quantity	100
Packaging Method	Bag & Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

 TE Part # 1-350589-0 STR/REL CLAMP NATL	 TE Part # 350811-1 STR/REL CLAMP	 TE Part # 643030-1 05P UMNL STR/REL	 TE Part # 1-480763-0 05P UMNL PLUG HSG NATL
 TE Part # 643406-3 05P UMNL PIN HDR ASS BLK 94VO	 TE Part # 794584-1 05P UMNL SOC HDR ASSY POL SN	 TE Part # 643030-2 05P UMNL STR/REL V2 NATL	 TE Part # 643030-3 05P UMNL STR/REL V2 NATL
 TE Part # 643030-4 05P UMNL STR/REL	 TE Part # 350848-5 05P UMNL PLUG TEST ASSY 94VO	 TE Part # 794920-1 05P UMNL SOCKER HDR ASSY POL	 TE Part # 926306-5 UMNL 5 WAY CAP HSG

Also in the Series | Universal MATE-N-LOK

 Circular Power Connectors(2)	 Connector Contacts(7)	 Insertion & Extraction Tools(4)	 Power Contacts(201)
 Rectangular Boots & Strain Relief(34)	 Rectangular Connector Adapters(7)	 Rectangular Connector Hardware(1)	 Rectangular Connector Housings(1)



Rectangular Connector Keying Plugs(3)



Rectangular Connector Seals(26)



Rectangular Power Connectors(662)

Customers Also Bought



TE Part #3-1879021-9
SMW3 3R9 5%



TE Part #350431-1
06P UMNL PIN HDR ASSY V2 NAT



TE Part #3-1415030-1
PB134024



TE Part #K1121749
Battery Disconnect 35-524-231-S-900



TE Part #1571610-1
Sealed R/A Tact switch, Sealed



TE Part #4-2319764-9
E STACK PIANO 8P G SHORT T&R PD OFF



TE Part #5164711-3
03pos.MINI-MATCH FBTB, 2.5mm pitch

Documents

Product Drawings

05P UMNL PIN HDR ASSY V2 NATL

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_640466-1_S.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_640466-1_S.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_640466-1_S.3d_stp.zip

English

3D PDF



English

Customer View Model

[ENG_CVM_640466-1_M.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_640466-1_M.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_640466-1_M.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY](#)

English

Product Specifications

[Application Specification - Universal MATE-N-LOK* Connectors](#)

English

Product Environmental Compliance

[MD_640466-1_04242018715_dmtec](#)

English

[MD_640466-1_04242018715_dmtec](#)

English

Instruction Sheets

[Instruction Sheet \(U.S.\)](#)

English