

NYLON-INSULATED DOUBLE CRIMP RING TERMINALS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16
AMP.	9	12	17	18

MAXIMUM ELECTRICAL RATING: 105 °C 600 VOLTS MAX.


INSULATION MATERIAL: NYLON

INSULATION COLOR:

22-16 A.W.G.: RED 

DOUBLE CRIMP: WITH COPPER SLEEVE ON BARREL

TERMINAL MATERIAL: COPPER



WIRE RANGE A.W.G. mm ²	ITEM NO.	STUD SIZE		DIMENSION ^{inch} mm							CRIMPING TOOL	Q'TY BOX		
		d2		W	F	L	E	D	d1	T				
22-16 A.W.G.	RNYD1-2	#2	.087 2.2	.217 5.5	.197 5.0	.713 18.1	.433 11.0	.177 4.5	.067 1.7	.030 0.75	IZUMI MODEL 34 WITH DIE INDEX COLOR:RED OR K.S. MODEL KST2000B WITH DIE INDEX COLOR:RED	1000		
	RNYD1-2.5	#2	.095 2.4		.189 4.8	.724 18.4						1000		
	RNYD1-3.2	#4	.126 3.2		.197 5.0	.728 18.5						1000		
	RNYDS1-3.7	#6	.146 3.7									1000		
	RNYDM1-3.7	#6	.146 3.7	.260 6.6	.248 6.3	.803 20.4						1000		
	RNYDL1-3.7	#6	.146 3.7	.315 8.0	.276 7.0	.858 21.8						1000		
	RNYDS1-4	#8	.169 4.3	.260 6.6	.248 6.3	.803 20.4						1000		
	RNYDL1-4	#8	.169 4.3	.315 8.0	.276 7.0	.858 21.8						1000		
	RNYD1-5	#10	.209 5.3									1000		
	0.5-1.5 mm ²	RNYDL1-5	#10	.209 5.3	.457 11.6	.433 11.0						1.094 27.8	.433 11.0	.177 4.5
RNYD1-6		1/4	.252 6.4					1000						
RNYD1-7		1/4	.291 7.4					1000						
RNYD1-8		5/16	.331 8.4					1000						
RNYDL1-8		5/16	.331 8.4	.535 13.6	.547 13.9	1.240 31.5	1000							
RNYD1-10		3/8	.413 10.5				1000							
RNYDL1-10		3/8	.413 10.5	.772 19.6	.630 16.0	1.433 36.4	1000							
RNYD1-12		1/2	.512 13.0					1000						
RNYD1-13		9/16	.591 15.0		.543 13.8			1000						
RNYD1-14		9/16	.591 15.0				1000							
RNYD1-16	5/8	.669 17.0	1.063 27.0	.827 21.0		1.783 45.3	1000							
RNYD1-20	3/4	.827 21.0			1000									

$(U_L) \subset (U_L)$ ALL LISTED